


(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
18 January 2001 (18.01.2001)

PCT

(10) International Publication Number
WO 01/04501 A1

- (51) International Patent Classification⁷: **F16B 41/00**, 23/00, 43/00
- (21) International Application Number: **PCT/AU00/00834**
- (22) International Filing Date: **12 July 2000 (12.07.2000)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
PQ 1580 **12 July 1999 (12.07.1999)** **AU**
- (71) Applicant (for all designated States except US): **GOOD-CART PTY LTD [AU/AU]**; 2/81 Bassett Street, Mona Vale, NSW 2103 (AU).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **RAWSON-HARRIS, Douglas [AU/AU]**; 2/81 Bassett Street, Mona Vale, NSW 2103 (AU).
- (74) Agent: **GRIFFITH HACK**; Level 8, 168 Walker Street, North Sydney, NSW 2060 (AU).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— With international search report.
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **SECURITY SCREW**

(57) **Abstract:** The present invention relates generally to a security screw (1) having threaded shank portion (2) and head portion (3). The head portion (3) is characterise by having a circular profile with a cylindrical peripheral wall (4) and a smooth crown (5) without any tool engagement slots, recesses or other profile in contrast to a convention screw. The security screw (1) is driven into place by way of a driving tool (9) having shank portion (10) adapted to be rotated by a suitable implement such as a power drill. The driving tool (9) further comprises a cup portion (13) incorporating a cylindrical recess (14) coaxial with the shank (10). The recess (14) is sized and shaped to fit over the head portion (3) of the screw (1).

WO 01/04501 A1